

SR46 MACHINECARD

DATE CUSTOMER



SR46



SR46: Semi-Automatic Random Cartons Sealing Machines

Standard

Taping Head K12/70	L	W	н
Min.	150	170	120
Max.	∞	650	650


Taping Head K12/50	L	W	н
Min.	150	170	100
Max.	∞	650	650

Any different dimension out of the standards above will be on request.

up to 900 Bph

Always based on shorter box manageable.

Operating Pressure Range	Air Consumption :
from 5,5 bar - to 7 bar	9 NI/cycle



TAPING UNIT POSITION

TOP + BOTTOM

TOP ONLY + BOTTOM PLATE


BOTTOM

MACHINE WORKING SIDE

LEFT SIDE


RIGHT SIDE

LEFT MACHINE



command side

RIGHT MACHINE



command side



WORKBENCH HEIGHT FROM 485 UP TO 825 mm

FROM 645 UP TO 980 mm

SPECIAL REQUEST FOR WORKBENCH HEIGHT

MACHINE ON WHEELS YES if yes please consider + 110 mm on workbench height

NO

POWER SUPPLY 380/415V 50Hz 3PH + N + PE

OTHER REQUEST, PLEASE SPECIFY

MACHINE COLORS STANDARD (as per photo)




ENVIRONMENT CONDITIONS (inside the company building)

- -ALTITUDE (LESS THAN 1000 M A.S.L.)
- -HIGH TEMPERATURE (NOT MORE THAN 40 °C)
- -LOW TEMPERATURE (NOT LESS THAN 5°C)
- -HIGH HUMIDITY (MORE THAN 80%)

ACCESSORIES ENERGY SAVING DEVICE (no need of PLC)

MACHINE LAYOUT(refferal dimensions)



SX - left version

DX - right version



BOXES INFORMATION: Note. standard weight range is 2- 30 kg, supposed for a product full box. Any other difference from these values should be evaluated by engineering department. In the last page the customer can check the general features required for the box.

WIDTH

LENGTH

EEECO

HEIGHT

WEIGHT OUTPUT

YES

NO

	FEFCO TYPE	LENGTH (mm)	(mm)	(mm)	(kg)	(BPM)	
BOX 1							
BOX 2							
BOX 3							
BOX 4							
BOX 5							
BOX 6							
BOX 7							
BOX 8							
BOX 9							
BOX 10							
WILL	THE CUST	OMER SUPP	LY BOXES TO	O BE TESTE	D?	YES	NO
	SIAT S.P.A		, 22 TURATE	(CO) ITALY		ATTENTION O Ated deliver	
IF YES	, HOW MA	NY TYPES O	F BOX DOES	THE CUSTO	OMER WAI	NT TO TEST?	
		3 TY	YPES - MAX 6	0 PIECES, T	ESTED FR	EE OF CHARG	Е
		FRO	OM 4 TO 10 T	YPES - MAX	100 TOTA	L PIECES, UNI	DER PAYMENT
		> 60	PIECES, UN	DER PAYM	ENT		
WILL THE CU (under payme			-			YES	NO

WILL SIAT INSTALL THE MACHINE?

(under payment)



CARTON TYPE					
FEFCO BOX TYPE					
BOX MODEL	0200 M/A	ж <u>г</u> в ж в ж в ж в ж в ж в ж в ж в ж в ж в			
	0201 M/A	# L B L B			
	SINGLE FLUTE				
CARDBOARD TYPE LAYERS STYLE	TWO LAYERS + SINGLE FLUTE	TANAN			
	THREE LAYERS + DOUBLE FLUTE				
	FOUR LAYERS + TRIPLE FLUTE				



CARDBOARD TYPE FLUTE STYLE	FLUTE "F"	Sannan
	FLUTE "E"	SAAAA
	FLUTE "C"	
	FLUTE "B"	
	FLUTE "A"	

FEFCO BOX TYPE				
1. GOOD TEXTURE OF CARTONS WITH SIDE FREE OF FOLDS 2. CREASE LINE WELL MARKED. PREFERABLY DOUBLE. 3. WHEN THE BOX IS CLOSED, FLAPS MUST NOT TOUCH THEMSELVES. MIN. 2 mm OF SPACE NEEDED. 4. MIN. WIDTH OF CUTS: 6 – 8 mm (see picture) 5. PLEASE ADVISE IN CASE OF USE OF SQUARE BOXES 6. PLEASE ADVISE IN CASE OF SPECIAL PROCESSING OF CARDBOARD (ex. die-cutting) 7. PLEASE ADVISE THE FEFCO BOX TYPE ACCORDING TO THE ABOVE CODIFICATION	> ■ < W = 6/8 min.			

	TAPING U	NIT PERFORMANCE	
	Α	MAX. 410 mm	
TAPE REEL DIMENSIONS	В	75 mm / 50 mm	1
	С	76 mm	→ B →

TAPE LEG					
	K11R / K12R	70 mm			
TAPE LEG DIMENSIONS	K11R / K12R	50 mm			
	K11/30 K12/30	30 mm			